

# S326

## High Precision Optical Fiber Cleaver



### Key Features

- Cleave anywhere
- Simple operation
- Easy fiber loading
- Durable and reliable design
- Wide lid opening
- Long blade life
- Light weight (About 30% reduced from previous model)
- High capacity waste bin (S326A)

With its ergonomic and light weight design, the S326 cleaver offers the operator the versatility to cleave on a work bench or in the palm of their hand. The reduced lid size and wide opening angle facilitates fiber loading and improves stability resulting in better single and ribbon fiber cleaves. Just pressing the lever completes the fiber cleave and automatically collects the waste. With 24 positions, the long life-time blade achieves 48,000 fiber cleaves. The S326 cleaver can offer optical fiber cleaving for a full range of OSP and OEM applications. The S326A configuration comes with both the regular and large size fiber waste bin or users can choose the smaller S326B option without a bin.



Operation on desktop



Operation on hand



Wide lid opening angle



## Specifications

<b>Fiber Types</b>	All fiber types
<b>Fiber Count</b>	Single to 12 ribbon fiber
<b>Clad Diameter</b>	125 µm
<b>Coating Diameter</b>	Single fiber: 250 to 900 µm Ribbon fiber: 280 to 400 µm (thickness)
<b>Cleave Length</b>	Single fiber: Fixed length 10 & 16 mm, Variable length 3 to 20 mm Ribbon fiber: Fixed length 10 mm
<b>Blade Life *1</b>	48000 fibers (2000 fibers×24 positions)
<b>Dimensions</b>	S326A: 96W×79D×56H mm S326B: 60W×79D×56H mm
<b>Weight</b>	S326A: 250 g S326B: 195 g

\*1: The blade life depends on the operation environment and condition. The number can vary and is not guaranteed.

## Standard Package

Item	P/N	Quantity	
		S326A	S326B
① S326A Main Body	S326A-01	1	—
② S326B Main Body	S326B-01	—	1
③ Single Fiber Adapter	S326X-11	1	1
④ Normal Fiber Waste Bin	S326X-12	2	—
⑤ Large Capacity Fiber Waste Bin	S326X-13	1	—
⑥ Semi-hard Case	S326X-14	1	—
⑦ Soft Case	S326X-15	—	1
⑧ Hexagonal Wrench	S326X-16	1	1
Operation Manual	FTS-B423	1	1



## Contact Us:

### FURUKAWA ELECTRIC CO. LTD.

#### Head Office:

2-3, Marunouchi 2-chome,  
Chiyoda-ku, Tokyo,  
100-8322, Japan  
TEL: + 81 3 3286 3227  
FAX: + 81 3 3286 3978  
[www.furukawa.co.jp](http://www.furukawa.co.jp)  
[comsales@ho.furukawa.co.jp](mailto:comsales@ho.furukawa.co.jp)

#### Europe:

**Furukawa Electric Europe, Ltd.**  
3rd Floor, Newcombe House  
43-45 Notting Hill Gate,  
London W11 3FE U.K.  
TEL: + 44 20 7313 5320  
FAX: + 44 20 7313 5310  
[www.furukawa.co.uk](http://www.furukawa.co.uk)  
[splicers@furukawa.co.uk](mailto:splicers@furukawa.co.uk)

#### North & South America:

**OFS Fitel, LLC**  
2000 Northeast Expressway  
Norcross, Georgia 30071, U.S.A.  
TOLL FREE: + 1 866 452 9516  
TEL: + 1 678 783 1090  
FAX: + 1 678 783 1093  
[www.ofsoptics.com](http://www.ofsoptics.com)  
[splicers@ofsoptics.com](mailto:splicers@ofsoptics.com)

#### China:

**Furukawa Shanghai, Ltd.**  
**Beijing Branch**  
1001A, Full Tower, No.09 Dong-  
sanhuang ZhongRoad, Chaoyang  
District, Beijing 100020, P.R. China  
TEL: + 86 10 8591 0608  
FAX: + 86 10 8591 0609  
[www.furukawa-sh.cn](http://www.furukawa-sh.cn)

#### South East Asia:

**Furukawa Electric Singapore**  
**Pte. Ltd.**  
10 Anson Road, #25-08  
International Plaza, Singapore  
079903  
Tel: + 65 6328 9870  
Fax: + 65 6224 2362  
[www.furukawa-sh.cn](http://www.furukawa-sh.cn)

#### Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in Japan. In addition, the Export Administration Regulations (EAR) of the United States may be applicable. In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of Japan or the Department of Commerce of the United States for details about procedures.

#### available from

**Optical Test and Calibration Ltd**  
+44 (0) 1274 393857  
[sales@otc.co.uk](mailto:sales@otc.co.uk)  
[www.otc.co.uk](http://www.otc.co.uk)