Drop Cable


ID: **Z262**

KABELOVNA Děčín Podmokly s.r.o.
Ústecká 840/33, 405 33 Děčín 5
Czech Republic
DIČ CZ26759993
tel.: +420 412 706 222
www.kabelovna.cz

29.7.2016 ver.8

J/A-VQ(BN)HH max. 2F

This cable is suitable for indoor or outdoor use.



Black FR-LSZH outer jacket, UV stable
(*Other colours available on request)*
Water blocking aramid yarn
FR-LSZH buffered optical fibre
FR-LSZH inner jacket, UV stable
Waterblocking E-glass

Mechanical and Environmental properties

Test		Value	Unit	Method
Cable outer diameter		6,4 ± 0,3	mm	EN 60811-1-1
Cable weight		41	kg/km	
Outer jacket thickness		0,8	mm	
Buffer diameter		0,9	mm	
Simplex diameter		2,0	mm	
Max. tensile strength		1000	N	EN 60974-1-2-E1
Crush resistance test		1000	N	EN 60974-1-2-E3
Impact resistance test		3	Nm	EN 60974-1-2-E4
Min. bend radius (no load)		5	mm	EN 60974-1-2-E11a
Min. bend radius (load)		10	mm	EN 60974-1-2-E11b
Temperature range	installation	-5 to + 50	°C	EN 60794-1-22-F1
	Operation	-20 to + 60	°C	
	Storage	-20 to + 60	°C	
Fire properties – Flammability		pass		EN60332-3-22 (cat.A)
				ČSN EN 50266-2-2
Fire properties – Acid gases		pass		EN 50267
				EN 50267-2-2
				EN 50267-2-3
				EN 60754-1
				EN 60754-2
Fire properties – Smoke density		pass		EN 61034-1
				EN 61034-2

Cable life time - minimum 30 years

Buffer

Tight	strip. up to 10 cm (xxTx)	
Colour	9/125	Yellow
	50/125	Green
	62,5/125	Blue
Material	FR-LSZH	

Other buffer colours available on request.

Simplex

1	Red
2	Black
Material	FR-LSZH

Other simplex colours available on request.


Sheat Marking

Print colour	White
Print method	INK-Jet
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

Other print legends available on request

Packing

Depending on ordered put-up lengths



KDP reserves the right to change the values in this document without prior notice.KDP is not responsible for any action taken pursuant to this document.This document is property of KDP. This document or any of its parts are not alowed to be redistributed without explicit consent of KDP.